

GSM Module for Reporting and Up/Download

ATS7310

ATS7310


The ATS7310 GSM module is directly connected to the Advisor MASTER panel and Advisor Advanced range and fully enables analogue alarm reporting and up- and downloading to TITAN via GSM.
 All reporting formats available through PSTN are available via GSM, including voice reporting or audio listen-in.
 The GSM module can be used for primary reporting as well as back-up reporting (using multiple central stations).

Specifications

Power supply	
Via ribbon cable from control panel	10 - 15 VDC
Via CON 1, BAT from backup battery	10 - 15 VDC
Current Consumption (at 13.8 VDC 5%)	
MI Bus	20 mA
GSM Online via battery leads	20 mA
GSM Online Max. via battery leads	0.3 A
Dimensions	
Battery type and max. capacity	lead acid rechargeable 18 Ah 12 V nom. (BS131)
Weight	44 gr.

Ordering Information

ATS1801	ATS Computer and printer interface
ATS1809	ATS Universal Interface for an Ethernet based IP connection
ATS7120	ATS ISDN - B channel communicator
ATS7121	ATS ISDN - B & D channels communicator
ATS7200N	ATS Voice Reporting Module
ATS7310	GSM Module for Reporting and Up/Download



- ◆ Full alarm reporting via GSM
- ◆ All popular reporting formats available, including voice reporting and audio listen-in
- ◆ Perfectly suitable for primary reporting in case a PSTN or ISDN line or IP connection is not available
- ◆ Back-up reporting easily configurable via multiple central stations
- ◆ Reliable data connection for Up/Download
- ◆ Unique 4800 Baud data connection for U/D
- ◆ Quad Band 900 / 1800 MHz
- ◆ Six status LED's for Diagnostics
- ◆ GSM Antenna included