




Member of



Certificate of Conformity with European standards for Components and Systems

Number of Certificate

Valid from
dd-mm-yyyy

Valid until
dd-mm-yyyy

EN-ST-000087

26-05-2015

25-05-2019

Subject matter of Certificate:

**Magnetic contact
MC 240 ap/up**

Owner of Certificate:

**Alarmtech Sweden AB
Alvägen 33
19133 SOLLENTUNA
SCHWEDEN**

Basis for certification:

EN 50131-2-6:2008

Use, the product disposes of the following parameters:

Intrusion and hold-up systems, Grade 2

The tests were carried out at VdS Schadenverhütung GmbH
and the results are documented in test report:

STE08/0107-EN-MC240

To guarantee the permanent quality of products a regular surveillance of the manufacturing process is performed.

This certificate comprises 4 pages and shall only be reproduced without any modifications and including all enclosures.

VdS Schadenverhütung GmbH
Zertifizierungsstelle
Amsterdamer Str. 174
D-50735 Köln

a company of the Gesamtverband
der Deutschen Versicherungs-
wirtschaft e.V. (GDV)

VdS Laboratories are accredited
by DAKKS according to
DIN EN ISO/IEC 17025
as a test laboratory.
The accreditation is valid
for the test methods listed
in the accreditation document



Deutsche
Akkreditierungsstelle
D-ZE-11149-01-01

Date: 13-05-2015

Managing director

Head of certification body



To Certificate No.: EN-ST-000087

Date : 13-05-2015

The approved component/system comprises the following parts:

Description of component	Type	Applicant's Registration No.	Approval number of component (only complete for system approval)
<p>Magnetic contact ap/up consisting of:</p> <ul style="list-style-type: none">- Magnetic switch for recessed mounting in aluminium housing with thread $\varnothing 10 \times 36\text{mm}$- bar magnet material ALNICO 500 $\varnothing 6 \times 30\text{mm}$ in aluminium housing with thread $\varnothing 10 \times 36\text{mm}$ <p>Optional Accessory:</p> <ul style="list-style-type: none">- plastic plug- plug with magnet NEO $\varnothing 10 \times 10\text{mm}$- Plastic housing (65x15x18)mm <p>Aluminium housing in:</p> <ul style="list-style-type: none">- (74x25x13)mm- (74x25x13)mm with magnet NEO $\varnothing 10 \times 10\text{mm}$- floor contact (102x40x15)mm- aluminium housing- (74x25x13)mm with magnet ALNICO $\varnothing 12 \times 60\text{mm}$- with magnet NEO $\varnothing 10 \times 10\text{mm}$- with magnet ALNICO $\varnothing 12 \times 60\text{mm}$- aluminium angle bracket- aluminium angle bracket	<p>MC 240 ap/up</p> <p>MC 200-1</p> <p>MC 200-2</p> <p>MC 200-3</p> <p>MC 200-4</p> <p>MC 200-5</p> <p>MC 200-6</p> <p>MC 200-7</p> <p>MC 200-11</p> <p>MC 200-12</p> <p>MC 200-13</p> <p>MC 200-14</p> <p>MC 200-15</p>		



To Certificate No.: EN-ST-000087

Date : 13-05-2015

The approved component/system is described as follows:

Type of document	Manufacturer's identification	Date	Number of Pages
Installation Manual:			
- Installation and User Manual	MC240	05.05.2012	1
- Systemübersicht/Errichter-handbuch		26.05.1993	6
- Bill of material	MC 240	26.05.1995	1
- Construction drawing MC240	MC 200-1	04.01.1992	1
- Reed Switch Specification	Coto FR2S series	24.02.2006	1
- Montageanleitung		20.09.2008	1
- Datablad NM Gjutharts	NM Gjutharts 347	11.03.1993	1
- Kennzeichnungsvorschlag		26.05.1993	1
- Systemübersicht Zubehör		26.05.1995	2
- Montageanleitung-Zubehör		26.05.1995	2
Drawings:			
- MC 200-1	3-200-1	29.04.1993	1
- MC 200-3	3-200-32	26.05.1995	1
- MC 200-4	4-200-4	02.04.1993	1
- MC 200-5	4-200-5	02.04.1993	1
- MC 200-6 C	4-200-6 C	02.04.1993	1
- MC 200-6 M	4-200-6 M	02.04.1993	1
- MC 200-7	4-200-7	02.04.1993	1
- Aluminiumwinkel, MC 400-1	4-400-1	02.04.1993	1
- Aluminiumwinkel, Z-Bracket	A3-200-16	02.04.1996	1



Enclosure 3

Sheet 1

To Certificate No.: EN-ST-000087

Date : 13-05-2015

Instructions for the application of the approval component/system (see enclosure 1):

1. The device should not be used in/on material with ferromagnetic properties.
2. The device complies with the requirements of SSF1014 and with Security Grade 2 of EN 50131-2-6 and Environmental Class IIIA according to EN 50130-5.