

PIR motion sensor 868 MHz Gen2

TX-2211-03-1

This wireless passive infrared motion sensor is equipped with a precision "Gliding Focus Curtain" mirror. It offers improved detection and better false immunity, using a custom ASIC with "4-dimensions" processing and an option to select bi-curtain processing.

Specifications

Detection range	16 m / 9 m
Coverage field of view	86° with 9 curtains
Undercrawl protection	Yes
Coverage pattern selection	Blinders and curtain labels
Mounting height	1.8 to 3.0 m
PIR process mode	Standard / Bi-curtain
Battery type	1 x 3V Lithium
Battery lifetime	More than 3 years
Operating Frequency	868 MHz
Compatible with	GE Security 868 MHz Gen2 receivers
Open-air range	400 m
Dimensions (L x W x D)	103 x 71 x 51 mm



Ordering Information

TX-2211-03-1 PIR motion sensor 868 MHz Gen2

- ◆ Learn-mode technology
- ◆ Volumetric coverage 10 / 16 m
- ◆ Precision "Gliding Focus Curtain" mirror
- ◆ Custom ASIC with "4D"-processing
- ◆ Bi-curtain processing for harsh environments
- ◆ More than 3 years battery life time
- ◆ Complies with EN50131-5-3 - approvals pending

