

AddSecure IRIS-4 2 Series



The IRIS-4 2 series are designed for commercial installations.

Enclosed in a practical and elegant housing, the IRIS-4 2 series deliver comprehensive solutions for IP based alarm transmission. Simplicity without compromising security, is the key feature of the IRIS-4 2series.

IRIS-4 2 Series

Other features AddSecure incorporated in the IRIS4 2series are:

Multiple IP transmission possibilities

The IRIS-4 2series is comprised out of 3 terminal variants

- IRIS-4 200 for single path 4G transmission
- IRIS-4 220 for single path IP transmission
- IRIS-4 240 for dual path IP+4G transmission

Complete compatibility

Through the wide range of interfaces, the IRIS-4 2series are compatible with any existing alarm control panel from whatever manufacturer.

- Dialport (emulated PSTN) connection supporting a broad range of analogue protocols such as Contact ID, SIA 0-4, Scancom fast format, CESA, Telim and Robofon
- RS-485, RS-232 and TTL bus connections for integration with leading manufacturers such as Honeywell, Texecom, Risco and many others.
- Logic inputs which can be programmed with alarm and restore messages in SIA, Contact ID or SMS text messages.

Fast and easy deployment

The IRIS-4 2series come standard with the renowned IRIS touch screen. Via the LCD touch screen, programming and commissioning of the IRIS-4 2series is realised in less than 3 minutes. Inter-active setup menu's in 7 possible languages guide the installer quickly through the installation process. Alternatively, the IRIS-4 2series can be programmed and commissioned with the IRIS Toolbox suite of software.



FEATURE	200	220	240
Fire retardant enclosure	●	●	●
Battery backup	-	-	-
Touch screen	●	●	●
Ethernet ports	-	1	1
WiFi	-	-	-
2/3/4G	●	-	●
Dial Capture	●	●	●
Relays	3	3	3
Inputs (pins)	4	4	4
Serial RS485	●	●	●
Serial TTL	●	●	●
RS232 (basic)	●	●	●
SMS text messaging	●	-	●
Multi language menus	●	●	●
VoIP & SIP services	●	●	●
CAN bus	-	-	-
EN54-21 CPR Fire approved	-	-	-

EN 50131, EN 50136 (VdS certified)
 The terminals are compliant with the requirements of European standards.
 EN 50131-1:2006+A2:2017 & EN 50131-10:2014
 EN 50136-1:2012 & EN 50136-2:2013
 ATS-SP6 over Ethernet, ATS-SP5 over 2/3/4G, ATS-DP4 (IRIS-4 240, 440 & 640)
 When using PSTN ATS-SP2 over PSTN, ATS-DP1 (IRIS-4 440)
 Environmental Class II