The AS368 is an extremely efficient base sounder that offers ultra-low power consumption. It offers a universal detector mounting platform for installation underneath any detector, but also allows the optional fitment of a blanking cover, to turn the unit into a slim and unobtrusive stand alone sounder.

Specifications

| Supply voltage | | |
|----------------------------|---------------------------|--|
| EN54-3 / fire applications | 17 - 60 VDC | |
| non-fire applications | 9 - 60 VDC | |
| Current consumption | | |
| (see tone table in manual) | 3 - 7 mA @ 24 VDC | |
| Sound output @ 1 meter | | |
| (see tone table in manual) | up to 95 dB(A) | |
| Tones | 32 | |
| Monitoring | Reverse polarity | |
| Temperature | -10°C to +55°C | |
| Construction | High impact polycarbonate | |
| Weight | 100g | |
| Colour | Red | |
| Ingress protection | IP21C | |
| Dimensions (x D) | 114 x 35 mm | |



| AS368 AS363W AS363W AS363M AS364W AS364W AS364W AS366 AS366W AS367 AS367 | Base sounder, multi tone, red Fire sounder, multi tone, shallow base Fire sounder, multi tone, shallow base, white Sounder, multi tone, shallow base, mains powered Fire sounder, multi tone, deep base Fire sounder, multi tone, deep base, white Sounder, multi tone, deep base, mains powered Sounder-beacon, multi tone, shallow base Sounder-beacon, multi tone, shallow base, white Sounder-beacon, multi tone, deep base |
|--|---|
| | Sounder-beacon, multi tone, deep base, white |
| AS368W | Base sounder, multi tone, white |



- Universal fixing platform for detector bases
- Low current consumption
- Blank cover for use as a stand alone sounder
- Reduced installation costs
- Two large cable entries
- High sound output
- Automatic synchronisation
- 32 Tones user selectable